

TECHNICAL Data Sheet



ATS984PU-L

4.0 Mil Ultra High Tack Silicone Splicing Tape w/ Liner

PRODUCT DESCRIPTION:

ATS984PU-L is a high tack silicone splicing tape with a PET liner that provides a high bond to silicone coated films and liners. This product is coated with an aggressive silicone adhesive that provides excellent quick stick to silicone release liners.

INDUSTRIES/CATEGORIES:

General Industrial, Masking, Splicing/Tabbing

PRODUCT INFORMATION:

Product Category	Backing Type	Adhesive Type	Liner Type	Color
Single Coated	Polyester	Solvent Silicone	PET	Purple

FEATURE BENEFITS:

- High Tack
- Chemical Resistance
- Removable and Repositionable

TYPICAL APPLICATIONS:

- Splicing
- Plating
- Film and Label Industry

PHYSICAL CHARACTERISTICS

Test Procedure	Nominal Values		Test Method
Total Thickness w/o Liner:	4.0 Mil	0.1016 mm	PSTC - 133
Backing Thickness:	2.0 Mil	0.0508 mm	PSTC - 133
Peel Adhesion (SS Panel):	32 oz/in	8.89 N/25.4 mm	PSTC - 101
Temperature Range:	Available Upon Request		

AVAILABLE SIZES

Product Configuration	Standard Size (Imperial)	Standard Size (Metric)
Master Roll:	54" x 1,512 Feet	1,372 mm x 461 M
Log Roll:	54" x 216 Feet	1,372 mm x 66 M
Slit Roll(s):	Available Upon Request	

LIMITED WARRANTY: Carolina Custom Products (CCP) warrants this product to be free of defects for a period of 18 months from the date of manufacture. These terms are in compliance with the Terms & Conditions of CCP Tapes. CCP Tapes reserves the right to properly address quality defections at their discretion. Furthermore, the user of the product shall assume all other risks including but not limited to; injury, damage, loss, misuse, or inability to properly use this product. Carolina Custom Products (CCP) disclaims any and all other warranties, expressed, or implied, including but not limited to the merchantability and fitness for a particular purpose.

STORAGE NOTE: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. CCP Tapes can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the product's suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with a relative humidity of 50%.
Form: WWW.TDSATS984PU-L V1

